

Ultimate Duty Spring Retractable Reels Air/Water/Oil/Grease - 1/4", 3/8", 1/2" I.D.

The ultra duty aluminum cast base and arm of the Series D8000 and E8000 offers the highest rigidity among this class of hose reels. Guide arms are field-adjustable for floor, wall, ceiling, pit and truck mounting. The durable baked-on, powder-coat finish provides a high quality ultra-violet radiation (sunlight) weather and chip-resistant finish.

For additional models, visit www.reelcraft.com



Series D8000 E reels are the same as D8000 O reels except **E Series reels are fully enclosed**. To order, change the model number suffix letter O to E. Example, D8650 OHP becomes D8650 EHP. Add 17 pounds to open reel weight.

Made in USA

DIMENSIONS	D/E8000 O		D/E8000 E	
	in	mm	in	mm
A	21 1/8	537	21 9/16	548
B	19	483	20 7/8	530
C	7 7/8	200	7 7/8	200
D	3 3/4	95	3 3/4	95
E	9 1/4	235	10 1/2	267

Inlet is 1/2" Outlet is 1/2" Four 1/2" (12.7mm) diameter mounting holes.

FEATURES

- ✓ Aluminum guide arm and base are cast from 40,000 P.S.I. tensile strength material with 7% elongation which assures ultimate shock resistance. Cast aluminum frame gives maximum strength with minimum payload weight.
- ✓ A special heavy, double adhesive sided spring case gasket protects the main spring from damage (failure) caused by water, dirt or other foreign matter entering the spring case.
- ✓ Guide arm is field adjustable for floor, wall, ceiling, pit and truck mounting.
- ✓ Full flow shaft and swivel.
- ✓ Reel springs are manufactured from the highest quality scale-less blue tempered steel.
- ✓ Individually coated components with a durable baked-on powder coat finish provides excellent high quality ultra violet radiation (sunlight) weather and chip-resistant finish.

MODELS WITH HOSE				HOSE CAPACITY					MODELS WITHOUT HOSE		
MODEL	WEIGHT	PRESSURE	I.D.	O.D.	(M)NPTF OUTLET	(F)NPTF INLET	LENGTH	MODEL	WEIGHT	PRESSURE	
	lbs / kg	psi / bar	in / mm	in / mm	in	in	ft / m		lbs / kg	psi / bar	
LOW PRESSURE AIR/WATER REELS Maximum Temperature 150° F (65° C) w/hose / 210° F (99° C) w/o hose											
D8650 OLP	48 22	300 21	3/8 10	.688 17	1/4	1/2	50 15	D8600 OLP	40 18	500 35	
D8670 OLP	52 24	300 21	3/8 10	.688 17	1/4	1/2	70 21	D8600 OLP	40 18	500 35	
D8850 OLP	52 24	300 21	1/2 13	.844 21	3/8	1/2	50 15	D8800 OLP	41 19	500 35	
E8850 OLP*	69 31	300 21	1/2 13	.844 21	3/8	1/2	50 15	E8800 OLP	58 26	500 35	
MEDIUM PRESSURE OIL REELS Maximum Temperature 210° F (99° C)											
D8650 OMP	53 24	2250 155	3/8 10	.690 18	1/2	1/2	50 15	D8600 OMP	41 19	3000 207	
D8840 OMP	53 24	2000 138	1/2 13	.815 21	1/2	1/2	40 12	D8800 OMP	41 19	3000 207	
D8850 OMP	56 25	2000 138	1/2 13	.815 21	1/2	1/2	50 15	D8800 OMP	41 19	3000 207	
E8850 OMP*	73 33	2000 138	1/2 13	.815 21	1/2	1/2	50 15	E8800 OMP	58 26	3000 207	
HIGH PRESSURE GREASE REELS Maximum Temperature 210° F (99° C)											
D8450 OHP	54 24	5000 345	1/4 6	.593 15	1/4	1/2	50 15	D8400 OHP	41 19	5000 345	
D8650 OHP	60 27	4000 276	3/8 10	.750 19	1/4	1/2	50 15	D8600 OHP	41 19	5000 345	
E8650 OHP*	74 34	4000 276	3/8 10	.750 19	1/4	1/2	50 15	E8600 OHP	58 26	5000 345	

*Series E8000 models are for lubrication trucks. Low pressure reels furnished standard with PVC hose. Medium pressure reels are furnished standard with S.A.E. 100 R1T one wire braid hose. High pressure reels furnished standard with SAE 100R2T two wire braid hose, suitable for grease applications only.