



Twin Hose, Spring Retractable Reels
Dual Hydraulic - 1/4", 3/8", 1/2" I.D.

Reelcraft's hydraulic reels are used for medium pressure dual hydraulic hose applications and are ideal for operating hydraulic cylinders, tools and equipment. High volume dual-body swivel for maximum product delivery (excluding the 80000). Series TH reels incorporate contemporary engineering and manufacturing techniques for trouble-free performance. Reels are all-steel construction and compact for applications with critical space requirements.

Made in USA

FEATURES

- ✓ Constant tension or pos-i-latch spool mechanism
- ✓ All-steel construction
- ✓ Reels have a durable, abrasion-resistant, baked-on powder coat finish spring motor
- ✓ Compact design for critical space requirements

	DIMENSIONS					
	TH5000 OMP		TH7000 OMP		TH80000 OMP	
	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm
A	14 1/2	368	20 1/4	514	25 3/8	645
B	13 1/2	343	19	483	24	610
C	9 3/4	248	7 7/8	200	10	254
D	2 1/2	64	3 7/8	98	6	152
E	6	152	7	178	13	330

C and D dimensions are mounting hole patterns. Four 5/16" (8mm) diameter mounting holes for the 5000 O. Four 1/2" (12.7mm) diameter mounting holes for the 7000 O and 80000.

**Questions?
We can help!**

Our friendly customer service team is ready to help you with expert assistance. When you call us, you get a live voice and fast, friendly service.

APPLICATIONS

- Cranes
- Construction Equipment
- Hydraulic Tools
- Vehicle Extraction Tools
- Aerial Device
- Hydraulic Cylinders
- Tree Cutters
- Digger Derricks
- Railroad Maintenance Tools

MODELS WITH HOSE				HOSE CAPACITY				MODELS WITHOUT HOSE			
MODEL	WEIGHT	PRESSURE	I.D.	O.D.	OUTLET	INLET	LENGTH	MODEL	WEIGHT	PRESSURE	
	lbs / kg	psi / bar	in / mm	in / mm	in	in	ft / m		lbs / kg	psi / bar	
MEDIUM PRESSURE HYDRAULIC HOSE REELS Maximum Temperature 210° F (99° C)											
TH5425 OMP	34 15	2000 138	1/4 6	.500 13	1/4 NPT(F)	1/4 NPT(F)	25 8	TH5400 OMP	24 11	3000 207	
TH7445 OMP	67 30	2000 138	1/4 6	.500 13	1/4 NPT(F)	1/4 NPT(F)	45 14	TH7400 OMP	47 21	3000 207	
THA7630 OMP	60 27	2000 138	3/8 10	.640 16	3/8 JIC(M)	3/8 NPT(F)	30 9	THA7600 OMP	47 21	3000 207	
MEDIUM PRESSURE HOSE REELS Maximum Temperature 210° F (99° C)											
TH86050 OMP	99 45	2000 138	3/8 10	.640 16	3/8 NPT(F)	3/8 NPT(F)	50 15	TH86000 OMP	87 39	3000 207	
TH88050 OMP	104 47	2000 138	1/2 13	.910 23	1/2 NPT(F)	1/2 NPT(F)	50 15	TH88000 OMP	87 39	3000 207	

Adjustable hose bumpers listed on page 47. See page 45 for optional accessories, mounting brackets and bases.