

General Use Hand Crank Series CU and H

Light Duty Hand Crank Reels Air/Water - 3/8" I.D.

Series CU reels are designed for lighter-duty applications that require longer lengths of low pressure air/water hose. Hand crank with a balanced brass swivel and brass inlet, Series CU is the product of lighter weight components and forward-thinking design. An economical choice for storing and retrieving hose.

SPECIFICATIONS

MODEL	HOSE I.D.		(M)NPTF OUTLET	(F)NPTF INLET	LENGTH		WEIGHT		PRESSURE	
	in / mm	in / mm	in	in	ft / m	ft / m	lbs / kg	lbs / kg	psi / bar	psi / bar
LOW PRESSURE AIR/WATER REELS: Maximum Temperature 150°F (65°C)										
CU6050LN	3/8	10	3/8	3/8	50	15	10	4.5	250	17
CU6100LN	3/8	10	3/8	3/8	100	30	13	6	250	17

Reels are supplied w/o hose; assemblies will be quoted upon request.

DIMENSIONS

	H16000		H18000		H28000		H28005		H29000		H29005		CU6050LN		CU6100LN	
	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm
A	19	483	19	483	20 1/8	512	11 1/2	292	11 1/2	292						
B	20	508	20	508	14	356	11	279	11	279						
C	15	381	15	381	10	254	2	51	2	51						
D	10	254	16	407	16	407	6	152	10 1/2	267						
E	12 1/2	318	18 1/2	470	18 1/2	470	11 1/4	286	15 5/8	397						
F	5 3/4	146	5 3/4	146	5 3/4	146	5 1/2	140	5 1/2	140						

SPECIFICATIONS

MODEL	HOSE I.D.		HOSE O.D.		(F)NPTF INLET	LENGTH		WEIGHT		PRESSURE	
	in / mm	in / mm	in / mm	in / mm	in	ft / m	ft / m	lbs / kg	lbs / kg	psi / bar	psi / bar
LOW PRESSURE AIR/WATER REELS Maximum Temperature 150°F (65°C)											
H16000	3/8	10	.688	17	3/8	300	91	32	15	500	35
H18000 CA	1/2	13	.844	21	1/2	200	61	33	15	1000	69
H28005	1/2	13	.844	21	1/2	300	91	34	15	1000	69
H28000	1/2	13	.844	21	1/2	300	91	37	17	1000	69
H19000	3/4	19	1.118	30	3/4	100	30	33	15	1000	69
H29005	3/4	19	1.118	30	3/4	100	30	35	16	1000	69
H29000	3/4	19	1.118	30	3/4	150	46	41	19	1000	69
MEDIUM PRESSURE OIL REELS Maximum Temperature 210°F (99°C)											
H16000 M	3/8	10	.690	18	3/8	300	91	32	15	3000	207
H18000 M CA	1/2	13	.815	21	1/2	200	61	35	16	3000	207
H19000 M CA	3/4	19	1.118	30	3/4	80	24	38	17	3000	207
H29000 M	3/4	19	1.118	30	3/4	125	38	35	16	3000	207
HIGH PRESSURE GREASE REELS Maximum Temperature 210°F (99°C)											
H16000 H	3/8	10	.750	19	3/8	250	76	32	15	5000	345

Reels are supplied w/o hose; assemblies will be quoted upon request.

CAUTION: To prevent drum damage fully extend and pressurize hose and rewind on the reel. Stainless models available. See page 16 and 17.



Light duty
CU6100LN



Light duty
CU6050LN



Medium duty
H16000

Medium Duty Hand Crank Reels Air/Water/Oil/Grease

3/8", 1/2", 3/4" I.D.

Series H is an economical reel designed for medium duty applications requiring long lengths of hose. It is equally suited for plant or field use such as turf care, pest control, steam cleaning and more. Shipped completely assembled, ready to install.

HoseReelSales.com
813-241-4900



REELCRAFT

Wind Things Up With Reelcraft™