



Nordics Series 5900

Large Frame Reels

Nordic™ Series 3700 and 5900

Heavy Duty Large Frame Reels

Nordic™ Series 3700 & 5900

2", 3" or 4" Fluid Path for 1½" through 4" I.D. Hose

Rewind: Gear-drive crank rewind or chain and sprocket drive powered by A.C. or D.C. electric motor, compressed air motor or hydraulic motor.

Inlet: 2" (Series 3700) / 3" (Series 5900) straight victaulic is standard. 4" (Series 5900) 90° victaulic and 24" diameter drum is standard. 90° victaulic swivel joint available at extra cost.

Gooseneck: 2" (Series 3700) / 3" (Series 5900) / 4" (Series 5900) female NPT. Other sizes and/or threads can be furnished and must be specified.

Series 5900 product temperatures from -50° F to +400° F and standard pressures to 300 p.s.i. Series 3700 standard seals maximum temperature 174° F (79° C) and minimum temperature -20° F (-29° C). Extreme temperature seals maximum temperature 400° F (204° C) and minimum temperature -50° F (-45° C).

Series 3700 and 5900 are shown with optional bevel crank.



Nordics Series 3700



Nordics Series 5900

1/2" pitch chain now standard

Standard pressures to 300 PSI Other temperatures or pressures can be furnished at extra cost, consult manufacturer. The standard color for this series is red or gray. ADD 12" to E dimension when crank is in rewind position.

Made in USA

HOSE I.D.	in mm	1 1/2	2	2 1/2	3	4
		38	51	64	76	102
HOSE O.D.	in mm	2.063	2.563	3.188	3.75	4.75
		52	65	81	95	121

SPECIFICATIONS - HOSE CAPACITY AND REEL DIMENSIONS

Refer to diagram on page 29 for dimension key.

KEY: CRK = hand crank; ELC = electric motor; HYD = hydraulic motor; AIR = air motor

MODEL	HOSE LENGTH				EST. WEIGHT		A	B	C	D	E CRK	E ELC	E AIR	E HYD	F CRK	F ELC	F AIR	F HYD	G	H
	ft	m	ft	m																
3700-23-20	65	25			114 LB	in	26	20	15	21	23	23	24	23	30	33	30	32	24½	13
	20	8			52 KG	mm	660	508	381	533	584	584	610	584	762	838	762	813	622	330
3700-25-20	65	55			124 LB	in	26	20	15	21	25	25	25	30	33	30	32	26½	14	
	20	17			56 KG	mm	660	508	381	533	635	635	635	635	762	838	762	813	673	356
3700-25-24	80	65			128 LB	in	30	24	15	21	25	25	25	34	37	34	36	26½	14	
	24	20			58 KG	mm	762	610	381	533	635	635	635	635	864	940	864	914	673	356
3700-25-32	115	90			136 LB	in	38	32	15	21	25	25	25	42	45	42	44	26½	14	
	35	27			62 KG	mm	965	813	381	533	635	635	635	635	1067	1143	1067	1118	673	356
3700-31-12	90	50			134 LB	in	18	12	15	24	31	31	31	22	25	22	24	32½	17	
	27	15			61 KG	mm	457	305	381	610	787	787	787	787	559	635	559	610	826	432
3700-31-20	165	90			142 LB	in	26	20	15	24	31	31	31	30	33	30	32	32½	17	
	50	27			64 KG	mm	660	508	381	610	787	787	787	762	838	762	813	826	432	
3700-31-26	220	125			148 LB	in	32	26	15	24	31	31	31	36	39	36	38	32½	17	
	67	38			67 KG	mm	813	660	381	610	787	787	787	787	914	991	914	965	826	432
3700-39-16	225	140			182 LB	in	22	16	15	24	39	39	39	26	29	26	28	40½	21	
	69	43			83 KG	mm	559	406	381	610	991	991	991	660	737	660	711	1029	533	
3700-39-24	350	220			190 LB	in	30	24	15	24	39	39	39	34	37	34	36	40½	21	
	107	67			86 KG	mm	762	610	381	610	991	991	991	864	940	864	914	1029	533	
5900-31-16	55	20	15		140 LB	in	22	16	20	24	31	31	31	26	29	26	28	32.5	17	
	17	6	5		64 KG	mm	559	406	508	610	787	787	787	660	737	660	711	826	432	
5900-31-24	85	30	25		150 LB	in	30	24	20	24	31	31	31	34	37	34	36	32.5	17	
	26	9	8		68 KG	mm	762	610	508	610	787	787	787	864	940	864	914	826	432	
5900-31-32	120	45	35		160 LB	in	38	32	20	24	31	31	31	42	45	42	44	32.5	17	
	37	14	11		73 KG	mm	965	813	508	610	787	787	787	1067	1143	1067	1118	826	432	
5900-36-12	60	30	30		146 LB	in	18	12	20	24	36	36	36	22	25	22	24	39	21	
	18	9	9		66 KG	mm	457	305	508	610	914	914	914	559	635	559	610	991	533	
5900-36-16	90	50	40	12	150 LB	in	22	16	20	24	36	36	36	26	29	26	28	39	21	
	27	15	12	4	68 KG	mm	559	406	508	610	914	914	914	660	737	660	711	991	533	
5900-39-12	90	50	35	15	180 LB	in	18	12	20	24	39	39	39	22	25	22	24	40.5	21	
	27	15	11	5	82 KG	mm	457	305	508	610	991	991	991	559	635	559	610	1029	533	
5900-39-16	135	80	50	15	200 LB	in	22	16	20	24	39	39	39	26	29	26	28	40.5	21	
	41	24	15	5	91 KG	mm	559	406	508	610	991	991	991	660	737	660	711	1029	533	
5900-39-24	200	120	65	25	210 LB	in	30	24	20	24	39	39	39	34	37	34	36	40.5	21	
	61	37	20	8	95 KG	mm	762	610	508	610	991	991	991	864	940	864	914	1029	533	

Refer to page 26 to build a complete model number. Refer to diagram on page 29 for dimension key.

HoseReelSales.com
813-241-4900



Wind Things Up With Reelcraft™