

# Multiple Configurations Safe-T-Reel™ Series

## Hand Crank Reels

Up to 150' fuel gas  
Up to 200' 12/3 cable

Ideal for applications where space, weight and flexibility are key, these reels are designed for manual winding of air/water/fuel gases hose, electric cord and welding cable. Versatile in function, select configurations to suit specific needs. Safe-T-Reels™ offer trouble-free management of large capacities of hose or cord.



**Dual Spool**  
Side-by-side combinations

T-2462-0

## Dual Spool

Stacked combinations  
T-2464-0



## Single Spool

Made in USA

### SINGLE SPOOL REELS

MODEL	AMP	REEL CAPACITY		WEIGHT	CABLE	A	B	E
		ft / m	lbs / kg					
<b>SINGLE WELDING CABLE 600 V</b>								
T-1460-0 <b>CA</b>	300	200	61	22	10	19 483	18 457	16 1/4 413
<b>SINGLE POWER CABLE - 3 CONDUCTOR</b>								
T-1535-003	30	150	45	22	10	8 / 3	19 483	18 457
T-1535-083-100*	33	100	30	50	23	8 / 3	19 483	18 457
T-1535-103-200*	24	200	61	81	37	10 / 3	19 483	18 457
T-1535-123-100*	25	100	30	46	21	12 / 3	19 483	18 457
T-1535-123-200*	20	200	61	71	32	12 / 3	19 483	18 457

\* includes cable

### DUAL SPOOL REELS

MODEL	AMP	REEL CAPACITY		WEIGHT	A	B	E
		ft / m	lbs / kg				
<b>DUAL SIDE-BY-SIDE WELDING CABLE (2) 600 V, 2/0 cable</b>							
T-2462-0 <b>QSA</b>	225	150	45	50	23	19 483	18 457
<b>DUAL STACKED WELDING CABLE (2) 600 V, 2/0 cable</b>							
T-2464-0 <b>QSA</b>	225	150	45	59	27	38 965	18 457
<b>DUAL SIDE-BY-SIDE POWER CABLE / AIR HOSE</b>							
T-2735-2-0*	35	200' / 150'	40	18	19	483	18 457

\* Air hose side has 1/2" (12.7mm) inlet

### SINGLE SPOOL REELS

MODEL	HOSE I.D.		HOSE O.D.		CAPACITY		WEIGHT		PRESSURE		A	B	E
	in / mm	in / mm	in / mm	in / mm	ft / m	lbs / kg	psi / bar	in / mm	in / mm	in / mm			
<b>SINGLE AIR/WATER</b> Maximum temperature 150° F (65° C)													
T-1115-08	1/2	13	.844	21	150	46	18	8	300	21	19 483	18 457	15 3/4 400
T-1116-08	1/2	13	.844	21	250	76	18	8	300	21	19 483	18 457	21 3/4 552
T-1117-12	3/4	19	1.188	30	50	15	22	10	250	17	19 483	18 457	15 3/4 400
T-1118-12	3/4	19	1.188	30	75	23	22	10	250	17	19 483	18 457	21 3/4 552
<b>SINGLE OXYGEN-ACETYLENE T-GRADE SEALS</b> Maximum temperature 150° F (65° C)													
T-1225-04 <b>CA</b>	1/4	6	.530	13	150	45	19	9	200	14	19 483	18 457	16 1/8 410
T-1225-04-100T	1/4	6	.530	13	100	30	44	20	200	14	19 483	18 457	16 1/8 410
T-1226-06	3/8	10	.625	16	100	30	19	9	200	14	19 483	18 457	16 1/8 410

**Caution:** Compressed air hoses should not be converted to oxygen service. Compressed air hoses are often contaminated with an oil coating, which can react explosively when oxygen is introduced. Oxygen/Acetylene cannot be combined with welding cable or power cord. **Note:** Models listed are without hose and/or cable. Weights listed above are actual product weight without packaging materials. Safe-T-Reels™ are available with cable or hose and in various combinations. Please consult Reelcraft customer service for additional information.



T-1225-04-100T  
Hose and cable not included.


**Detail of heavy duty shaft**  
with tapered roller bearing for high rigidity




Shaft sizes are 1 to 1.25" in diameter, supported by tapered roller bearings with 2 to 2.3" housings.

### DIMENSIONS


MODEL	DIMENSIONS	
	C	D
inches		
T-1115 / T-1117	6	6.5
T-1225 / T-1226	6	6.5
T-1460 / T-1535	6	6.5
T-1116 / T-1118	6	12.5



T-2462	6	6.5
T-2735	6	6.5



T-2464	6	6.5
--------	---	-----



All reels have four 1/2" (13 mm) diameter mounting holes

HoseReelSales.com  
813-241-4900



**REELCRAFT**

Wind Things Up With Reelcraft™