

Replacement Hose Assemblies Partial list

PART NUMBER	I.D.	O.D.	LENGTH/PRESSURE		BRAID	END FITINGS		WGT
	in	in	ft	psi		inches		
LOW PRESSURE Air and water								
601001-25	1/4	.500	25	300	Nylon Braid	¼ x ¼	NPTF(M)	3.0
601001-35	1/4	.500	35	300	Nylon Braid	¼ x ¼	NPTF(M)	3.2
601013-25	3/8	.640	25	300	Nylon Braid	¼ x ¼	NPTF(M)	4.5
S601013-35	3/8	.640	35	300	Nylon Braid	¼ x ¼	NPTF(M)	4.7
601013-50	3/8	.640	50	300	Nylon Braid	¼ x ¼	NPTF(M)	6.0
601017-70	3/8	.640	70	300	Nylon Braid	½ x ¼	NPTF(M)	7.9
601015-100	3/8	.640	100	300	Nylon Braid	½ x ¾	NPTF(M)	18.3
601017-50	3/8	.640	50	300	Nylon Braid	½ x ¼	NPTF(M)	6.0
601021-50	1/2	.781	50	300	Nylon Braid	½ x ¾	NPTF(M)	10.5
601022-50	1/2	.781	50	300	Nylon Braid	½ x ½	NPTF(M)	10.5
601022-100	1/2	.781	100	300	Nylon Braid	½ x ½	NPTF(M)	25.0
601026-50	3/4	1.062	50	250	Nylon Braid	¾ x ¾	NPTF(M)	15.0
601026-75	3/4	1.062	75	250	Nylon Braid	¾ x ¾	NPTF(M)	19.1
601027-50	1	1.281	50	250	Nylon Braid	1 x ¾	NPTF(M)	21.8
MEDIUM PRESSURE Oil and petroleum fluids								
12-260043	3/8	.713	25	2250	1 Wire	3/8 x 3/8	NPTF(M)	6.0
16-260043	3/8	.713	30	2250	1 Wire	3/8 x 3/8	NPTF(M)	7.1
7-260043	1/2	.846	40	2000	1 Wire	½ x ½	NPTF(M)	11.7
8-260043	1/2	.846	50	2000	1 Wire	½ x ½	NPTF(M)	14.1
HIGH PRESSURE Chassis grease								
7-260044	1/4	.691	30	5000	2 Wire	¼ x ¼	NPTF(M)	7.7
9-260044	1/4	.691	50	5000	2 Wire	3/8 x ¼	NPTF(M)	12.7
13-260044	3/8	.777	25	4000	2 Wire	¼ x ¼	NPTF(M)	9.7
5-260044	3/8	.840	50	4000	2 Wire	3/8 x ¼	NPTF(M)	19.2
TWIN WELDING ¼" Oxygen-acetylene								
601032-25	¼ dual		25	200	1 Fabric	9/16-18	LH/RH (F)	6.5
601032-50	¼ dual		50	200	1 Fabric	9/16-18	LH/RH (F)	12.1
601032-60	¼ dual		60	200	1 Fabric	9/16-18	LH/RH (F)	13.3
601032-100	¼ dual		100	200	1 Fabric	9/16-18	LH/RH (F)	24.2
TWIN WELDING ¼" 'T' Grade								
601031-25	¼ dual		25	200	1 Fabric	9/16-18	LH/RH (F)	6.5
601032-50	¼ dual		50	200	1 Fabric	9/16-18	LH/RH (F)	12.11
601031-60	¼ dual		60	200	1 Fabric	9/16-18	LH/RH (F)	14.41
601031-100	¼ dual		100	200	1 Fabric	9/16-18	LH/RH (F)	24.21

CAUTION: Be sure working pressure required does not exceed above ratings. Misapplication can result in serious operator injury. **NOTE:** Advise product to be handled, maximum temperature and pressure fitting size or sizes when ordering.



601022-50
**AIR & WATER
HOSE ASSEMBLY**

Two Year Limited Warranty

Reelcraft now offers a two year limited warranty. All products manufactured by Reelcraft Industries, Inc. are warranted to be free of defects due to faulty material or workmanship for 24 months from date of shipment, except hose. Normal wear and tear is not considered a defect in material or workmanship. Reelcraft's liability shall be limited to repair or replacement of defective material during the warranty period and will be at Reelcraft's discretion when returned pre-paid to its plant or authorized service depot. The warranty does not cover damage caused by accident, abuse, neglect or improper installation. Reelcraft products must be installed, maintained and operated in accordance to the recommendation of Reelcraft and the manual of instructions. Failure to use circuit breakers on electric motors, filter, lubricators on air motors and flexible inlet connections will void warranty. Equipment, products, components and hoses not manufactured by Reelcraft are subject to the original manufacturer's guarantee and warranties. Hoses carry a six month warranty as listed by the manufacturer. Reelcraft will assist in filing claims, but does not have any additional responsibility if original manufacturer denies warranty claim. Products built to customer specifications and requirements, Nordic Series and Series 40 or products incorporating variation from cataloged items are considered special and are not subject to cancellation or returnable for credit under any circumstances. Reelcraft reserves the right to modify or alter product, dimensions, design and construction to improve performance.

NOTE: For complete warranty information, online warranty registration, service manuals, and return information please visit www.reelcraft.com.

Return Policy

Materials/products returned pre-paid to Reelcraft for warranty inspection/consideration and found to be defective will be repaired/replaced at no charge to the customer per Reelcraft's discretion. Materials/products deemed not defective will require customer authorization to repair or replace at customer's expense.

Warranty Return Protocol:

1. Contact Reelcraft customer service at 1-800-444-3134 and request an authorization number. Warranty claims will require the following information before a return

authorization number (RGA) can be issued.

- A. Product/model number.
- B. Serial number.
- C. Invoice number.

Additional information regarding the specific reason for return will be required to process requests.

2. If a replacement is required prior to Reelcraft receiving your return, the items being sent will be invoiced to your account until the warranty process is completed.
3. Once given an RGA number, all corresponding inquiries, paperwork and boxes will require this number. Reelcraft reserves the right to refuse returns without an RGA number.

4. Upon receipt of your warranty return and all the warranty conditions are met, a credit memo will be issued to your account and forwarded for your records. If there is a problem with your return, a customer service representative will contact you to discuss it further.

5. If you desire, a warranty report is available to be forwarded or discussed with you regarding your specific return and Reelcraft's findings. Please contact Reelcraft's Customer Service Department toll-free: 1-800-444-3134.

NOTE: For complete warranty information, online warranty registration, service manuals and return information please visit www.reelcraft.com.